



BLUE STAR



MADE TO DELIVER
BEST-IN-CLASS PRESERVATION.

Hermetic Series

Refrigeration Systems



Blue Star, India's leading refrigeration company, offers a complete range of evaporating and condensing units. These units are designed to deliver superior cooling for food preservation and are equipped to deliver temperatures for various applications.

The balanced selection of the evaporator and condensing units assures delivery of capacity. The matching controllers with refrigeration units support each installation and enable the controlling and monitoring of temperature. Each Blue Star installation comes with a weather-proof power panel that allows for easy, speedy, safe and long-lasting power connection. So when it comes to cold storage, trust in the experts for reliable, efficient and trouble-free refrigeration.





Evaporating Units

Blue Star's evaporators are compact and sleek. The evaporator is housed within the cold storage and occupies minimum space. This allows you to utilise the maximum volume of cold storage.

Features:



Stainless steel body (SS304) for enhanced durability and strength



Improved air throw for uniform air distribution



Excellent corrosion resistance



External rotor driven fans have low noise levels and conform to IP45 standards



Inner grooved copper tubes for superior heat transfer



Removable side panels for easy service and minimum downtime



4 FPI coil for medium & low temperature units



Defrost heaters within the coil to ensure total defrost



Condensing Units



Blue Star's condensing units are characterised by high-efficiency heat transfer and low power consumption.

Features:



Energy-efficient scroll and reciprocating compressors



Pre-charged unit with service valves



Powder coated body makes these units UV and corrosion-resistant



Safety and control devices for better system protection



Inner grooved copper tubes and slit aluminium fins for superior heat transfer



Weather-proof polyester powder coated canopy



Filter drier for moisture and dirt protection



Thermally protected and permanently lubricated fan motors



Smaller footprint for ease of handling and installation

Controller

Positive Room Temperature Controller:

Features:

- Specifically designed for refrigeration applications
- Controls compressor cut off and temperature
- Fault alarm indication
- Two-compressor controller with separate set points and differentials



Medium & Negative Room Temperature Controller:

Features:

- 4 digit, 1" dot matrix display
- Precise temperature range : – 50.0°C to + 50.0°C and resolution 0.1° C
- Computer connectivity over RS485
- HP/LP, AUX faults for compressor protection
- Defrost heater operation based on compressor run time



Power Panel

Blue Star's Refrigeration Units come with ready-to-use power panels that make electrical connections simple, fast and long-lasting.

Features:

- Embedded switchgear in the Positive Temperature Condensing Unit
- Power Panel with necessary accessories and defrost controls is available for Medium & Low Temperature Units

Technical Specifications

High Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at +4°C Room Temperature											
Description/ Model	Units	RUAH00 614KP -I	RUAH01 014KP -I	RUAH01 514KP -I	RUAH02 014KP -I	RUAH 02014 -I-N	RUAH03 014CS -I-N	RUAH04 014CS -I-N	RUAH06 024CS -I-N	RUAH06 014CS -I-N	RUAH08 024CS -I-N	RUAH08 014CS -I-N	RUAH 12014 -I
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	20,000	30,000	40,000	60,000	60,000	80,000	80,000	1,20,000
Power Supply	V/Ph/ Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	85	140	250	380	815	815	815	815	1630
	Qty	1	2	3	4	3	2	2	2	2	2	2	2
Airflow	CFM	800	1600	2400	3200	3905	4580	5230	12000	12000	11700	11700	17480
Air Throw	Feet	12	14	16	16	16	25	40	45	45	45	45	98.5
No. of Circuits	Nos.	1	1	1	1	1	1	1	2	1	2	1	1
Overall Dimen- sions (WxDxH)	mm	864x480 x450	1245x480 x450	1780x480 x450	2210x480 x450	1626x404 x522	1707x646 x718	1707x646 x718	2142x841 x956	2142x841 x956	2142x841 x956	2142x841 x956	2863x840 x1356
Dry Weight	kgs	18	25	35	45	56	75	85	140	140	150	150	350

Blue Star Outdoor Unit		Cooling Capacities at +4°C Room Temperature										
Description/ Model	Units	RUAH OP0614	RUAH OP1014	RUAH OP1514	RUAH OS2014	RUAH OS3014	RUAH OS4014	RUAH OS3014 x 2Nos	RUAH OS6014	RUAH OS4014 x 2 Nos	RUAH OS8014	RUAH OS12014
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	30,000	40,000	2 x 30,000 =60,000	60,000	2 x 40,000 =80,000	80,000	1,20,000
Compressor Type	-	Hermetic Recip	Hermetic Recip	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1	1	1 in each chassis	1	1 in each chassis	1	1
No. of such Chassis	Nos.	1	1	1	1	1	1	2 x RUA- HOS3014	1	2 x RUA- HOS4014	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	910x370 x560	910x370 x560	910x370 x560	1082x 464 x657	1082x 464 x1261	1082x 464 x1261	1082x 464 x1261	1532x654 x947	1082x 464 x1261	1532x654 x947	1450x880 x1115
Each Chassis Dry Weight	kgs	51	61	80	110	125	132	125	185	132	190	275
Each Chassis Refrigerant Pre- charged Qty	kgs	1.2	1.6	2	2.5	3.5	4	3.5	8	4	9	12

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/+4°C Room Temp /10SH.
Units tested up to 50°C ambient as per standard.

Technical Specifications

High Temperature Air-Cooled Refrigeration System with R410A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at +4°C Room Temperature			
Description/Model	Units	RUAH00611-I	RUAH01011-I	RUAH01511-I	RUAH02011-I
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50
Fan Motor	Watt	85	85	85	85
	Qty	1	2	3	4
Airflow	CFM	800	1600	2400	3200
Air Throw	Feet	12	14	16	16
No. of Circuits	Nos.	1	1	1	1
Overall Dimensions (WxDxH)	mm	864x480x450	1245x480x450	1780x480x450	2210x480x450
Dry Weight	kgs	18	25	35	45

Blue Star Indoor Unit		Cooling Capacities at +4°C Room Temperature			
Description/Model	Units	RUAHOR00611	RUAHOR01011	RUAHOR01511	RUAHOR02011
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000
Compressor Type	-	Hermetic Rotary	Hermetic Rotary	Hermetic Rotary	Hermetic Rotary
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50
Comp. Quantity	Nos.	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	894x370x556	894x370x556	894x370x556	1083x464x653
Each Chassis Dry Weight	kgs	42	48	70	80
Each Chassis Refrigerant Precharged Qty	kgs	1.2	1.3	1.7	2

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/+4°C Room Temp /10SH.
Units tested up to 50°C ambient as per standard.

Technical Specifications

High Temperature Air-Cooled Refrigeration System with R410A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at +18°C Room Temperature				
Description/Model	Units	RUAH03611-I	RUAH06611-I	RUAH10211-I	RUAH13211-I	RUAH13221-I
Nominal Capacity	Btu/hr	36,000	66,000	1,02,000	1,32,000	1,32,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	380	815	815	815
	Qty	4	2	2	2	2
Airflow	CFM	3200	5230	12000	11700	11700
Air Throw	Feet	16	40	45	45	45
No. of Circuits	Nos.	1	1	1	1	1
Overall Dimensions (WxDxH)	mm	2210x480x450	1707x646x718	2142x841x956	2142x841x956	2142x841x956
Dry Weight	kgs	45	85	140	150	150

Blue Star Outdoor Unit		Cooling Capacities at +18°C Room Temperature				
Description/Model	Units	RUAHOR3611	RUAHOS6611	RUAHOS10211	RUAHOS13211	RUAHOS6611 x 2Nos
Nominal Capacity	Btu/hr	36,000	66,000	1,02,000	1,32,000	2 x 66,000=1,32,000
Compressor Type	-	Hermetic Rotary	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1 in each chassis
No. of such Chassis	Nos.	1	1	1	1	2 x RUAHOS6611
Each Chassis Overall Dimensions (WxDxH)	mm	1071x464x655	1089x484x925	1417x451x925	1514x651x919	1089x484x925
Each Chassis Dry Weight	kgs	80	90	150	190	90
Each Chassis Refrigerant Precharged Qty	kgs	2	4	5	6	4

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/+18°C Room Temp /10SH.
Units tested up to 50°C ambient as per standard.

Technical Specifications

Medium Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at -5°C Room Temperature			
Description/Model	Units	RUAM01214-I-N	RUAM01514-I-N	RUAM02014-I-N	RUAM03514-I-N
Nominal Capacity	Btu/hr	12,000	15,000	20,000	35,000
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	380
	Qty	2	3	4	2
Airflow	CFM	1600	2400	3200	5500
Air Throw	Feet	14	16	16	40
No. of Circuits	Nos.	1	1	1	1
Overall Dimensions (WxDxH)	mm	1250x480x440	1780x480x440	2210x480x440	1710x645x720
Dry Weight	kgs	37	45	58	89

Blue Star Outdoor Unit		Cooling Capacities at -5°C Room Temperature			
Description/Model	Units	RUAM01214-O	RUAM01514-O	RUAM02014-O	RUAM03514-O
Nominal Capacity	Btu/hr	12,000	15,000	20,000	35,000
Compressor Type	-	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1100x464x660	1100x464x660	1100x464x1260	1100x464x1260
Each Chassis Dry Weight	kgs	83	86	131	136
Each Chassis Refrigerant Precharged Qty	kgs	2.5	2.5	3.5	4

Note: Specifications are subject to change without prior notice.

Cooling capacity at the rated condition 35 Amb Temp/-5°C Room Temp /10SH.

Units tested up to 50°C ambient as per standard.

Technical Specifications

Low Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at -23°C Room Temperature				
Description/Model	Units	RUAL00614-I-N	RUAL00914-I-N	RUAL01214-I-N	RUAL01814-I-N1	RUAL02414-I-N
Nominal Capacity	Btu/hr	6,000	9,000	12,000	18,000	24,000
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	380	815
	Qty	2	3	4	2	2
Airflow	CFM	1600	2400	3200	5500	11700
Air Throw	Feet	14	16	16	40	45
No. of Circuits	Nos.	1	1	1	1	1
Overall Dimensions (WxDxH)	mm	1245x480x450	1780x480x450	2210x480x450	1707x646x718	2142x841x956
Dry Weight	kgs	37	45	58	89	135

Blue Star Outdoor Unit		Cooling Capacities at -23°C Room Temperature				
Description/Model	Units	RUAL00614S-O-N1	RUAL00914S-O-N1	RUAL01214S-O-N1	RUAL01814S-O-N1	RUAL02414S-O-N1
Nominal Capacity	Btu/hr	6,000	9,000	12,000	18,000	24,000
Compressor Type	-	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1222x539x669	1222x539x669	1240x539x962	1240x539x962	1240x539x962
Each Chassis Dry Weight	kgs	105	115	117	135	148
Each Chassis Refrigerant Precharged Qty	kgs	2.5	3	4	5	6

Blue Star Outdoor Unit		Cooling Capacities at -23°C Room Temperature	
Description/Model	Units	RUAL00614P-O	RUAL00914P-O
Nominal Capacity	Btu/hr	6,000	9,000
Compressor Type	-	Hermetic Recip	Hermetic Recip
Power Supply	V/Ph/Hz	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1
No. of such Chassis	Nos.	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1222x539x669	1222x539x669
Each Chassis Dry Weight	kgs	80	93
Each Chassis Refrigerant Precharged Qty	kgs	2.5	3

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/-23°C
Room Temp /10SH Units tested up to 50°C ambient as per standard.

Notes

[illegible]



Scan QR code for
Blue Star Customer Care
App available on
App Store & Google Play.



SMS "SERVICE" to 57575.



Scan QR code to reach
out on WhatsApp.
24x7 Customer Care
on +91 89 7678 1177.



To know more about Blue Star, visit
www.bluestarindia.com, email us at
coolingsolutions@bluestarindia.com
or SMS "COOL" to 57575.

For more information, please contact **BLUE STAR LIMITED** • **Ahmedabad** 201 to 205, Unicus Shyamal, Shyamal Cross Rd, Balgayatri Society Part-2, Satellite, Shyamal, Ahmedabad: 380015 Phone: (+91) (79) 4022 4000 • **Bengaluru** Anjuman Kay Arr Tower, No 28, Ward No 77, Mission Road, Bengaluru - 560027 Phone: (+91) (80) 4185 4000 • **Bhubaneswar** 3A, Satya Nagar, 2nd Floor, Bhubaneswar - 751007 Phone: (+91) (674) 2572 403 / 2573 670 / 2570 024 • **Chandigarh** 6th Floor, Sanjeev Tower, Plot No 55, Industrial & Business Park, Phase 1, Chandigarh - 160002 Phone: (+91) (172) 415 5100 • **Chennai** KRM Plaza, No.2, Harrington Road, Chetpet, Chennai - 600031 Phone: (+91) (44) 4244 4000 • **Coimbatore** Krisan Workspaces, Mayflower Valencia, 4th Floor, Nava India Rd, Coimbatore - 641004 Phone: (+91) (422) 437 7125 • **Goa** 210, 2nd Floor, Gera's Imperium I, Patta, Panjim, Goa - 403001 Phone: (+91) (832) 243 8171 / 243 7287 • **Gurugram** 6th Floor, Vatika Atrium, Golf Course Road, Sector 53, Gurugram - 122002 (Haryana) Phone: (+91) (124) 409 4000 • **Guwahati** 5th Floor, 503, Roodraksh Mall, GS ROAD, Bhangaghar, Dispur, Guwahati, Kamrup Metropolitan, Assam - 781005 Phone: (+91) (361) 246 8496 • **Hyderabad** Ashoka Raghupati Chambers, No 1-10-60 to 64, 4th Floor, S P Road, Begumpet, Hyderabad - 500016 Phone: (+91) (40) 4400 4000 • **Indore** Office No 502, Maloo-01 26/C, Scheme No 94/C Ring Road, Indore - 452010 Phone: (+91) (731) 400 1211 / 400 1311 • **Jaipur** 607-B, 6th Floor, Man Upasana Plaza, Sardar Patel Marg, Jaipur - 302001 Phone: (+91) (141) 431 3000 • **Kochi** Prestige TMS Square, 9th Floor, No. 2, Service Road, Padivattom, Edappally, Kochi - 682024 Phone: (+91) (484) 449 9000 • **Kolkata** Eco Centre Business Tower, 11th Floor, Unit No: 1 & 2, Plot No 4, EM Block, Sector V, Salt Lake, Bidhannagar, Kolkata - 700091 Phone: (+91) (33) 4081 5400 • **Lucknow** 5th Floor, BBD Viraj Tower, TCG-1 A-V3, Vibhuti Khand, Gomti Nagar, Lucknow, Uttar Pradesh - 226010 Phone: (+91) (522) 403 4000 • **Ludhiana** Goshawk Rental Space Solutions Pvt Ltd, BX-3369, Sandhu Tower 2, 2nd Floor, Gurdev Nagar, Ferozepur Road, Ludhiana - 141001 • **Mumbai** Blue Star House, 9A, Ghatkopar, Link Road, Sakinaka, Mumbai - 400072 Phone: (+91) (22) 6668 4000 • **Nagpur** 219 Bajaj Nagar, 1st Floor, South Ambazari Road, Nagpur - 440010 Phone: (+91) (712) 662 4000 • **New Delhi** Unit No 201 & 202, Baani Corporate One, Plot No 5, Second Floor, District Centre, Jasola, New Delhi - 110025 Phone: (+91) (11) 4149 4000 • **Patna** The Hub, 2nd floor, Near Regent cinema, Gandhi Maidan Road, Patna - 800004 • **Pune** 201/A, Nityanand Complex, 247/A Bund Garden Road, Pune - 411001 Phone: (+91) (20) 4104 4000 / 2616 7230 • **Raipur** MM Silver Plaza, Office No. 103, 1st Floor, Opp Udyog Bhavan, Ring Road No. 1, Raipur - 492001 Phone: (+91) (771) 428 0900 • **Surat** WorkspaceCo (The He Ha Studio), 4th Floor, Kalp Business Centre, Opp. Lavanya Mall, Citylight, Surat - 395007 • **Thane** Blue Star Limited, Blue Star Innovation Centre, Next to Hotel Vihangs Inn, Kapurbavdi, Ghodbunder Road, Thane West - 400607 Phone: (+91) (22) 3508 4000 • **Thiruvananthapuram** TC IV/962, Chandrika, Sree Chitra Nagar, Pipe line Road, Kawdiar, Thiruvananthapuram - 695003 Phone: (+91) (471) 243 5025 • **Vadodara** INCUSPAZE Office Spaces, 3rd Floor Alembic 1965, Alembic City, Gorwa-Alembic Road, Vadodara - 390003 Phone: (+91) (265) 661 4000 / 265 233 2021 / 22 • **Vijayawada** No 40-1-62, Nagas Hafeez Plaza, Opposite to grand modern supermarket, Near BENZ Circle, MG. Road, Vijayawada - 520010 Phone: (+91) (866) 248 4004 • **Visakhapatnam** Qubexpro Business Centre, V Mall, Lifestyle Building, 4th Floor, Facor Layout, Waltair Uplands, Visakhapatnam - 530003 Phone: (+91) (891) 668 6705.



Blue Star products comply with RoHS regulations as per E-Waste (Management & Handling) Rules, 2016. For disposal of E-Waste, kindly visit our website www.bluestarindia.com or call our customer care on +91 89 7678 1177.